



**Aviation  
Ground  
Equipment Corp.**

**5000 Series  
Electric**




## **90-180 kVA – 400 Hz (28 VDC, 270 VDC)\* Facility Power Converter**

The Facility Power Converter (FPC) is a vertically mounted, solid state power converter designed for flight deck conditions as well as land based theaters. The FPC converts 380/440 VAC 50/60 Hz input power to 115 VAC 400 Hz, 270 VDC and 28 VDC aircraft power.

### **Standard Features:**

- AC Output: 115/200 VAC, 400 Hz, 72 kW max per output, Meets MIL-STD-704F
- DC Output: 28 VDC, 600 A Continuous, 2000 A Peak, Meets MIL-STD-704F\*
- DC Output: 270 VDC Main, 72 kW, Meets LMCO F-35 Requirements\*
- Smart Control User Interface
- Built-In Test Diagnostics (BIT) with Fault Recording
- Pedestal Mount (Available Upon Request)

**\*Denotes Optional Specification**



### **Aviation Ground Equipment Corp.**

324 South Service Road, Suite 104, Melville NY USA • 230 Industrial Drive, Franklin OH  
USA Tel: +1(631)815-5520 Fax: +1(631)815-5526 Toll Free: +1(800)758-0044  
Email: sales@aviationgroundequip.com Cage Code: OTZM0  
Web: www.aviationgroundequip.com



# Aviation Ground Equipment Corp.

## 5000 Series Electric

### Specifications

#### 115/200 VAC 400 Hz. Output

- Meets or Exceeds MIL-STD-704F
- Ratings: 90 -180kVA @ 0.8 PF)
- Overloads: 110% - 60 minutes  
125% - 5 minutes
- Meets all Military and Commercial Requirements for No-Brake Power Transfer (NBPT)
- Voltage Regulation:  $<\pm 1\%$  up to rated load
- THD (Total Harmonic Distortion):  $< 3\%$
- IHD (Individual Harmonic Content):  $< 2\%$
- Transient Performance Meets and Exceeds MIL-STD-704F
- Output Voltage Adjustment Range:  $\pm 15\%$
- Phase Voltage Displacement with Balanced Load:  $< 2\%$
- Phase Voltage Balance (with 10% Unbalanced Load on a Single Phase):  $< 3$  volts
- Line Drop Compensation: automatic up to 8% (user adjustable)

#### 28 VDC Output (Optional)

- Meets or Exceeds MIL-STD-704F
- 28.5 VDC Transformer-Rectifier
- Ratings: 600 amps continuous  
2000 amps starting current
- Overloads: 125% - 5 minutes  
150% - 5 seconds
- Fully Adjustable Current Limiting
- Voltage Regulation:  $<\pm 1\%$  up to rated load

#### 270 VDC Main Output (Optional)

- Meets or Exceeds F-35 (JSF) Specifications as recognized by LMCO
- Meets or Exceeds MIL-STD-704F
- Ratings: 72 kW (continuous)
- Overloads: 125% - 5 minutes  
200% - 5 seconds
- Fully Adjustable Current Limiting
- Integrated Unit-Cable Interlock

#### Environmental

- Temperature, MIL-STD-810F Method 501.4, 502.4 Operating  $-40^{\circ}\text{F}$  to  $+125^{\circ}\text{F}$  ( $-40^{\circ}\text{C}$  to  $+52^{\circ}\text{C}$ ); Non-Operating  $-60^{\circ}\text{F}$  to  $+160^{\circ}\text{F}$  ( $-51^{\circ}\text{C}$  to  $+71^{\circ}\text{C}$ )
- Humidity, MIL-STD-810F, Method 507.4
- Salt Fog, MIL-STD-810F, Method 509.3
- Blowing Rain, MIL-STD-810F, Method 506.4
- Blowing Sand, MIL-STD-810F, Method 510.4
- Wind, MIL-STD-810F, Method 506.10
- Vibration, MIL-STD-167-1
- Rail Impact, MIL-STD-810F 516.5
- Air Transportability

#### Military & Commercial Standards

- MIL-STD-704F
- MIL-STD-167-1
- MIL-STD-810F
- MIL-STD-209
- MIL-STD-889
- MIL-STD-1472
- SAE AS 50881
- F-35 (JSF) LMCO (Approved)

#### Dimensions & Weight

- Dimensions 42"H X 43"W X 79"L
- Weight 2250 lbs.

#### Maintenance

- Mean Time to Repair  $< 120$  minutes

#### Protection

- AC Output: Over/Under Voltage, Over/Under Frequency, Overload
- DC Outputs: Over/Under Voltage, Overload, Short Circuit
- Internal: Door Interlock, Contactors Stuck (Open/Closed), Internal Power Supply Voltage, Converter Fail

#### Controls / Indicators

- Smart Control User Interface
- Sealed, tactile feedback membrane panel
- Integrated Built-In Test (BIT)
- Front Control Panel
  - Fault Code Display with Indicators
  - Adjustable Brightness Indicator Lamps with ON/OFF
  - LED Display Input/Output
    - Voltage
    - Amperage
    - Frequency
  - Cable Interlock Status Indicators
  - Line Drop Comp, User Adjustable
  - Output Voltage, User Adjustable
  - Emergency Stop Switch
- Door Interlock Switch
- Elapsed Time Hour Meter

Specifications subject to change without notice

Datasheet REV 08-19-2017

#### Aviation Ground Equipment Corp.

324 South Service Road, Suite 104, Melville NY USA • 230 Industrial Drive, Franklin OH  
USA Tel: +1(631)815-5520 Fax: +1(631)815-5526 Toll Free: +1(800)758-0044 Email:  
sales@aviationgroundequip.com Cage Code: OTZM0  
Web: www.aviationgroundequip.com

