



**Aviation
Ground
Equipment Corp.**

**5000 Series
Electric**



90 - 180 kVA – 400 Hz (28 VDC, 270 VDC)* Mobile Frequency Converter

The Mobile Frequency Converter is a four wheeled, manually propelled vehicle designed for flight deck conditions as well as land based theaters. The cart features an integrated power frequency converter that converts 380/440 VAC 50/60 Hz input power to 115 VAC 400 Hz, 270 VDC and 28 VDC aircraft power.

Standard Features:

- AC Output: 115/200 VAC, 400 Hz, 72 kW, Meets MIL-STD-704F
- DC Output: 28 VDC, 600 A Continuous, 2000 A Peak, Meets MIL-STD-704F*
- DC Output: 270 VDC Main, 72 kW, Meets LMCO F-35 Requirements*
- Smart Control User Interface
- Built-In Test Diagnostics (BIT) with Fault Recording
- Rugged Four-Wheeled Trailer, Hand Brake System, SAE AS 8090, Type II, Group C

*Denotes Optional Requirement



Aviation Ground Equipment Corp.

324 South Service Road, Suite 104, Melville NY • 230 Industrial Drive, Franklin OH
Tel: +1(631)815-5520 Fax: +1(631)815-5526 Toll Free: +1(800)758-0044
Email: sales@aviationgroundequip.com Cage Code: OTZM0
Web: www.aviationgroundequip.com



Aviation Ground Equipment Corp.

5000 Series Electric

Specifications

Facility Input

- 440/460 VAC, 3-Phase, 60Hz or 380 VAC, 3-Phase, 50Hz
- Input Phase Rotation Insensitive
- 3 Wire Ungrounded Type 1 Power

115/200 VAC 400 Hz. Output

- Meets or Exceeds MIL-STD-704F
- Ratings: 90-180kVA@ 0.8 PF)
- Overloads: 110% - 60 minutes
125% - 5 minutes
- Meets all Military and Commercial Requirements for No-Brake Power Transfer (NBPT)
- Voltage Regulation: $\pm 1\%$ up to rated load
- THD (Total Harmonic Distortion): $< 3\%$
- IHD (Individual Harmonic Content): $< 2\%$
- Transient Performance Meets and Exceeds MIL-STD-704F
- Output Voltage Adjustment Range: $\pm 15\%$
- Phase Voltage Displacement with Balanced Load: $< 2\%$
- Phase Voltage Balance (with 10% Unbalanced Load on a Single Phase): < 3 volts
- Line Drop Compensation: automatic up to 8% (user adjustable)

28 VDC Output (Optional)

- Meets or Exceeds MIL-STD-704F
- 28.5 VDC Transformer-Rectifier
- Ratings: 600 amps continuous
2000 amps starting current
- Overloads: 125% - 5 minutes
150% - 5 seconds
- Fully Adjustable Current Limiting
- Voltage Regulation: $< \pm 1\%$ up to rated load

270 VDC Main Output (Optional)

- Meets or Exceeds F-35 (JSF) Specifications as recognized by LMCO
- Meets or Exceeds MIL-STD-704F
- Ratings: 72 kW (continuous)
- Overloads: 125% - 5 minutes
200% - 5 seconds
- Fully Adjustable Current Limiting
- Integrated Unit-Cable Interlock

Environmental

- Temperature, MIL-STD-810F Method 501.4, 502.4 Operating -40°F to $+125^{\circ}\text{F}$ (-40°C to $+52^{\circ}\text{C}$); Non-Operating -60°F to $+160^{\circ}\text{F}$ (-51°C to $+71^{\circ}\text{C}$)
- Humidity, MIL-STD-810F, Method 507.4
- Salt Fog, MIL-STD-810F, Method 509.3
- Blowing Rain, MIL-STD-810F, Method 506.4
- Blowing Sand, MIL-STD-810F, Method 510.4
- Wind, MIL-STD-810F, Method 506.10
- Vibration, MIL-STD-167-1
- Rail Impact, MIL-STD-810F 516.5
- Air Transportability
- Tie Down, MIL-T-81259B

Military & Commercial Standards

- MIL-STD-704F
- MIL-STD-167-1
- MIL-STD-810F
- MIL-STD-209
- MIL-STD-889
- MIL-STD-1472
- SAE AS 50881
- F-35 (JSF) LMCO (Approved)

Dimensions & Weight

- Dimensions 42"H X 43"W X 79"L
- Weight 2250 lbs.

Maintenance

- Mean Time to Repair < 120 minutes

Protection

- AC Output: Over/Under Voltage, Over/Under Frequency, Overload
- DC Outputs: Over/Under Voltage, Overload, Short Circuit
- Internal: Door Interlock, Contactors Stuck (Open/Closed), Internal Power Supply Voltage, Converter Fail

Controls / Indicators

- Smart Control User Interface
- Sealed, tactile feedback membrane panel
- Integrated Built-In Test (BIT)
- Front Control Panel
 - Fault Code Display with Indicators
 - Adjustable Brightness Indicator Lamps with ON/OFF
 - LED Display Input/Output
 - Voltage
 - Amperage
 - Frequency
 - Cable Interlock Status Indicators
 - Line Drop Comp, User Adjustable
 - Output Voltage, User Adjustable
 - Emergency Stop Switch
- Door Interlock Switch
- Elapsed Time Hour Meter

Specifications subject to change without notice

Datasheet REV 08-19-2017